

## SK-120

HYDROCARBON RESIN SK-120 is a low molecular weight, pale yellow thermoplastic resin, produced from petroleum-derived monomers.

### Typical Properties

Softening Point (R&B), °C	120+/-5	(ASTM E28)
Color, Gardner 50% resin solid in toluene	10max.	(ASTM D1544)
Bromine Number, Br g/100g	25max.	(ASTM D1159)
Acid Value, KOH mg/g	0.1max.	(ASTM D664)
Specific Gravity, @25 °C	1.05~1.10	(ASTM D71)
Ash Content	0.05% max.	(ASTM 2415)

### Suggested Application

#### 1. Paint

##### Key Application

In the production of Anti-corrosive coating, Alkyd Enamel and Vanish, widely used in the ships, industry and furniture

#### 2. Adhesives

In the production of adhesives for edge veneer and for bonding wood or similar materials to chipboard in the furniture industry

#### 3. Print ink

Newspapers (particularly color sections), Magazines, Folding Cartons (cereal boxes, for example), Metal Containers (cans)

#### 4. Asphalt

Colorful asphalt and high speed road asphalt.

### Outstanding Characteristics

It is soluble or dispersible in aromatic hydrocarbons, esters and chlorinated solvents. It is only partially soluble in ketone and insoluble in glycols and water.

### Package and Supply

- 25 kg paper bag
- 500 kg jumbo bag

### Storage and Inventory Control

Indoor storage is strongly recommended.

Storage at temperatures above 30°C should be avoided.

All information showed in this data sheet is based on our careful examinations and investigations. We can not assume any responsibility in connection with the individual use of our products, nor do we warrant against any loss or damages directly caused by the individual use of our products.